



## Main

Product or Component Type	Elbow
Range	I-Line

## Complementary

Rated Current	3000 A
Busbar Material	Copper busbar
Busbar Position	Edgewise
Integral Ground	50 percent capacity integral ground bus High short-circuit bracing
Rated Operational Voltage	600 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
Length	279.40 mm (11 in)
Height	11 in (279.40 mm)

## Ordering and shipping details

Category	20043-3000A/3200A CU FEEDER BUS IP54 THER
Discount Schedule	PE8
GTIN	00785901275626
Returnability	No
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------