

NEER EMT Straps

For EMT.

1901 and 1807: One Hole Click-On

Application

- Click-on type one hole straps for EMT provides support for conduit, as required by the National Electrical Code.

Material/Finish


- Steel/zinc plated

Certifications and Compliances

- UL Standard: 2239
- 1901 through 1906
UL Listed: E333806
- CSA Standard: C22.2 18.4
- 1901 through 1903
cUL Listed: E333806



1901



TH-1901 and TH-1807: Two Hole Snap-On

Application

- Snap-on type two hole straps for EMT are used where higher load bearing supports are desired.

Material/Finish


- Steel/zinc plated

Certifications and Compliances

- TH-1901 through TH-1905
UL Standard: 2239
UL Listed: E333806
CSA Standard: C22.2 18.4
cUL Listed: E333806



TH-1901



| Trade Size (Inches) | Catalog Number | Dimensions in Inches/Millimeters | | | |
|---------------------|----------------|----------------------------------|----------------|---------------|---------------|
| | | A | B | C | D |
| 1/2 | 1901 | 1.64/ 41.7 | 0.80/ 20.3 | 0.57/ 14.5 | 0.28/ 7.1 |
| 3/4 | 1902 | 1.96/ 49.8 | 0.98/ 24.9 | 0.63/ 16.0 | 0.28/ 7.1 |
| 1 | 1903 | 2.22/ 56.4 | 1.13/ 28.7 | 0.75/ 19.1 | 0.28/ 7.1 |
| 1-1/4 | 1904 | 2.86/ 72.6 | 1.50/ 38.1 | 0.87/ 22.1 | 0.38/ 9.7 |
| 1-1/2 | 1905 | 3.14/ 79.8 | 1.75/ 44.5 | 0.99/ 25.1 | 0.38/ 9.7 |
| 2 | 1906 | 3.89/ 98.8 | 2.00/ 50.8 | 1.11/ 28.2 | 0.44/ 11.2 |
| 2-1/2 | 1807 | 4.99/ 126.7 | 2.85/ 72.4 | 1.24/ 31.5 | 0.53/ 13.5 |
| 3 | 1808 | 5.55/ 141.0 | 3.47/ 88.1 | 1.25/ 31.8 | 0.53/ 13.5 |
| 3-1/2 | 1809 | 6.25/ 158.8 | 4.10/ 104.1 | 1.25/ 31.8 | 0.53/ 13.5 |
| 4 | 1810 | 7.00/ 177.8 | 4.51/ 114.6 | 1.26/ 32.0 | 0.53/ 13.5 |

| Trade Size (Inches) | Catalog Number | Dimensions in Inches/Millimeters | | | |
|---------------------|----------------|----------------------------------|----------------|---------------|---------------|
| | | A | B | C | D |
| 1/2 | TH-1901 | 2.17/ 55.1 | 0.72/ 18.3 | 0.56/ 14.2 | 0.19/ 4.8 |
| 3/4 | TH-1902 | 2.71/ 68.8 | 0.91/ 23.1 | 0.61/ 15.5 | 0.19/ 4.8 |
| 1 | TH-1903 | 3.10/ 78.7 | 1.12/ 28.4 | 0.68/ 17.3 | 0.19/ 4.8 |
| 1-1/4 | TH-1904 | 3.70/ 94.0 | 1.44/ 36.6 | 0.74/ 18.8 | 0.25/ 6.4 |
| 1-1/2 | TH-1905 | 4.24/ 107.7 | 1.67/ 42.4 | 0.87/ 22.1 | 0.25/ 6.4 |
| 2 | TH-1906 | 4.83/ 122.7 | 2.13/ 54.1 | 1.00/ 25.4 | 0.38/ 9.7 |
| 2-1/2 | TH-1807 | 5.98/ 151.9 | 2.87/ 72.9 | 0.98/ 24.9 | 0.38/ 9.7 |
| 3 | TH-1808 | 6.37/ 161.8 | 3.56/ 90.4 | 0.99/ 25.1 | 0.38/ 9.7 |
| 3-1/2 | TH-1809 | 7.37/ 187.2 | 4.05/ 102.9 | 1.00/ 25.4 | 0.44/ 11.2 |
| 4 | TH-1810 | 8.12/ 206.2 | 4.51/ 114.6 | 1.00/ 25.4 | 0.44/ 11.2 |