

Raintight Conduit Hubs

Threaded for Rigid Conduit & IMC

Type CHM & Type CHM - T

Use:

Type CHM - General Purpose Fitting.

Type CHM-T - Insulated Throat form with Bonding Locknut.

Features:

- Male thread type
- Tapered female thread for rigid conduit and IMC
- Recessed O-ring seal assures watertight and dust tight connections
- Type CHM-T with insulated throat and bonding locknut is suitable for service entrance application

Material/Finish:

Malleable Iron/Zinc Electroplated

Optional Finish:

For additional corrosion protection, specify

Mechanically Galvanized

Contact your local representative for pricing and availability.

Third Party Certification:



UL Listed: 11853

UL Listed as suitable for wet locations.



CSA Certified: 009795

Raintight.

Suitable for use in hazardous locations as follows:

Class I, Div. 2

Class II, Div. 1, 2

Class III, Div. 1, 2

Per NEC 501-4(b), 502-4(a), 503-3(a)

Applicable Third Party Standards:

UL Standard: 514B

CSA Standard: C22.2 No. 18

Fed. Spec: W-F-408E

• NEMA: FB-1


• NEMA: 4

• NEMA: 12

Note:


Minimum wall thickness that can be accommodated is $\frac{1}{32}$ ".

		Dimensions in Inches					
Trade Size (inches)	Catalog Number	A	B	C	D	Max. Box Wall Thk.	
					Female Tapered N.P.T.		
½	CHM-50	⅞	1½	½	½ - 14	⅜ ₁₆	
¾	CHM-75	1	1¾	½	¾ - 14	⅝ ₈	
1	CHM-100	1⅝	2	⅝	1 - 11½	⅞ ₁₆	
1¼	CHM-125	1¼	2⅜	⅝	1¼ - 11½	1⅜ ₃₂	
1½	CHM-150	1¼	2¾	⅝	1½ - 11½	1⅝ ₃₂	
2	CHM-200	1¼	3¼	¾	2 - 11½	⅞	
2½	CHM-250	1⅝	3⅞	1	2½ - 8	⅞ ₁₆	
3	CHM-300	1¾	4⅝	1	3 - 8	⅞	
3½	CHM-350	1⅞	5⅝	1⅝	3½ - 8	⅞	
4	CHM-400	1⅞	5⅝	1⅝	4 - 8	1⅜ ₁₆	
5	CHM-500	2⅝	6⅞	1¾	5 - 8	1⅜ ₁₆	
6	CHM-600	2⅝	8⅞	1¾	6 - 8	1⅜ ₁₆	



Type CHM

Trade Size (inches)	Insulated Throat Catalog Number	Dimensions in Inches					Max. Box Wall Thk.
		A	B	C	D Female Tapered N.P.T.		
½	CHM-50T	⅞	1½	½	⅓ - 14	⅞ ₃₂	
¾	CHM-75T	1	1¾	½	¾ - 14	⅞ ₃₂	
1	CHM-100T	1⅛	2	⅝	1 - 11½	1⅜ ₃₂	
1¼	CHM-125T	1¼	2⅜	⅝	1¼ - 11½	1⅜ ₃₂	
1½	CHM-150T	1¼	2¾	⅝	1½ - 11½	1⅜ ₃₂	
2	CHM-200T	1¾	3¼	¾	2 - 11½	⅞	
2½	CHM-250T	1⅞	3⅞	1	2½ - 8	2⅜ ₃₂	
3	CHM-300T	1¾	4⅞	1	3 - 8	1⅜ ₁₆	
3½	CHM-350T	1⅞	5⅞	1⅛	3½ - 8	¾	
4	CHM-400T	1⅞	5⅞	1⅛	4 - 8	1⅜ ₁₆	
5	CHM-500T	2⅞	6⅞	1¼	5 - 8	1⅜ ₁₆	
6	CHM-600T	2⅞	8⅞	1¼	6 - 8	1⅜ ₁₆	



Type CHM-T

