

Product data sheet

Characteristics

9065SP34

Motor Logic Plus Solid State Overload Relay Size 3 20-90A 480VAC



Main

Range of product	Motor Logic Plus
Product destination	Starter
Thermal overload type	Solid state

Complementary

NEMA size	3
Phase	3 phase
Mounting support	Mounting plate
[Ue] rated operational voltage	480 V AC
Maximum Height	3.05 in (77.5 mm)
Maximum Width	3.85 in (97.8 mm)
Maximum Depth	5.04 in (128 mm)

Ordering and shipping details

Category	18061 - SPARE PARTS DISCOUNT CP1
Discount Schedule	CP1
GTIN	00785901367901
Nbr. of units in pkg.	5
Package weight(Lbs)	1.48 lb(US) (0.67 kg)
Returnability	No
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.