Product data sheet Characteristics

9012GDW4G18

9012G, pressure switch 9012 g, fixed scale, 1 threshold, 1.5 to 75 PSIG



Main	
Range of Product	9012G
Pressure sensor type	Electromechanical pressure switch
Pressure sensor name	9012G
Pressure Rating	75 psi (517.11 kPa)
Maximum pressure	240 psi
Contacts type and composition	NC-NO, SPDT-DB, Form Z, snap action, silver nickel contacts
Controlled fluid	Hydraulic oil -40250 °F (-40121 °C)) Non-corrosive liquids Air Non-corrosive gas
Fluid connection type	0.25 inch 18 NPTF UL 508
Pressure switch type of operation	Detection of 1 single threshold
Scale type	Fixed
Local display	Without

Complementary

Complementary		
Range on decreasing pressure	1.575 psi (10.34517.11 kPa)	
Approx fix differential at mid range	3 psi (20.68 kPa) +/- 2.5 % full scale	
Cable entry	0.5 inch NPT conduit entrance	
Terminal block type	4 screw terminals	
Electrical connection	Screw-clamp terminals, AWG 22AWG 12	
Electrical circuit type	Control circuit	
Local signalling	1 neon red) 120 V AC/DC 105125 V)	
Line Rated Current	6 A 120 V AC 0.22 A 125 V DC	
Setting	Internal	
Enclosure Material	Die cast aluminium alloy 380	
Pressure actuator	Diaphragm nitrile (Buna-N)	
Height	5.55 in (140.97 mm)	
Depth	3.11 in (78.99 mm)	
Width	3.5 in (88.90 mm)	
Operating position	Any position	
Materials in contact with fluid	Nitrile (Buna-N) Zinc plated steel	
Short-circuit protection	10 A cartridge overload and short-circuit protection gL	
Maximum operating rate	120 cyc/mn	
Mechanical durability	5000000 cycles	
Repeat accuracy	4 %	
Net Weight	3 lb(US) (1.36 kg)	

Environment

Vibration resistance	2 gn 40150 Hz)IEC 68-2-6	
Shock resistance	50 gn IEC 58-2-27	
Standards	UL 508 CE CSA C22.2 No 14	
Product Certifications	CE UL listed file E12158 CCN NKPZ and CCN NTHT CSA LR25490 class 3211 03	
NEMA degree of protection	NEMA 4/4X/13 UL 50	
Ambient air temperature for operation	-10185 °F (-2385 °C)	

Ordering and shipping details

Category	21522 - 9012 G INDUSTRIAL PRESSURE SWITCHES
Discount Schedule	CP7G
GTIN	785901773702
Nbr. of units in pkg.	1
Package weight(Lbs)	3.00 lb(US) (1.361 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	24.13 in (61.29 cm)	
Package 1 width	9.50 in (24.13 cm)	
Package 1 Length	61.29 in (155.677 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

٧	Varranty	18 months	